

DESCRIPTION

PRODRY 35

Fabr.year: 2014

- New boxed
- Pcs available: 7
- Price: € 650.- net FCA

(50500350)



FEATURES

- The ProDry TD dehumidifier has a solid metal body work.
- Stackable construction.
- Automatic stop when the water container is full.
- Equipped with an hour counter, hygostat and a defrosting system.

ADVANTAGES

- A condensate pump is available as an accessory.
- The air filter can be easily cleaned and replaced.

APPLICATIONS

- Dehumidifying after water damage because of leakage.
- Drying of areas in construction sites or renovation projects.
- Management of humidity level.

WORKING PRINCIPLE

Areas are dehumidified according to the condensation principle.

TECHNICAL SPECIFICATIONS

MODEL	Capacity (l-24hr)		Capacity (l-24hr)		Operating range		Air flow (m³ /h)	Power consumption 230 V (AMPS)	Tank capacity (l)	ITEM NUMBER
	Max.	25 °C/65% RV	30 °C/85% RV	°C	% RV					
ProDry 35	30	17.2	26.8	2-32	35-100	350	2.7	6	50.500.350	
ProDry 55	55	35.0	53.0	2-32	35-100	600	3.5	6	50.500.550	
ProDry 80	80	48.0	80.0	2-32	35-100	850	4.8	-	50.500.800	
Multibar tube (p.m.)									00.003.207	

Dimensions ProDry only (cm)								Dimensions including packing (cm)			
A	B	C	D	E	F	KG		L	B	H	KG
ProDry 35	-	-	82	54	55	-	35	60	53	68	38
ProDry 55	-	-	96	54	55	-	38	63	54	78	43
ProDry 80	-	-	115	60	71	-	61	65	70	67	65



