

PRODUKTSPEZIFIKATIONEN BX/TBD 18



BX 15

BX 9

BX 3



BX 20/30



TBD 18 PC



TECHNISCHE DATEN | ABMESSUNGEN UND GEWICHTE

1 kW = 860 kcal/h 1 kW = 3.413 Btu/h 1 kW = 3,6 mJ/h 1 kg = 1,2 l/h

MODELL	BX 3	BX 9	BX 15	BX 20	BX 30	TBD 18 PC
Bestellnummer	40.107.005	40.107.015	40.107.020	40.107.021	40.107.022	40.017.100
Schädlingsbekämpfung						*
Heizleistung (kW)	3	9	15	20	30	18
Regelmöglichkeit (kW)	0-2-3	0-4,5-9	0-7,5-15	0-10-20	0-20-30	0-9-18
Versorgungsspannung (V)	230	3x400	3x400	3x400	3x400	3x400
Nennstrom (A)	8,9-13,2	6,8-13,3	11,2-21,9	15-29,5	43,4	14-26
Delta T (°C)	38	36-28	42	32	47-34	20
Luftleistung (m³/St)	220	700-900	1.000	1.750	1.900	3.960
230 volt Stecker	*					
400 volt 16 Amp Stecker		*				
400 volt 32 Amp Stecker			*			*
Thermostat eingebaut	*	*	*	*	*	*
Thermostatanschluss extern						*
Tragegriff	*	*	*	*	*	
Aufhängbügel	*	*	*			
Fahrgestell						*
Zusammengebaut LxBxH (cm)	37x28x33	37x35x45	39x52x49	61x57x57	61x57x57	176x70x83
In Verpackung LxBxH (cm)	36x28x34	40x36x49	40x36x49	51x44x69	51x44x69	120x87x105
Gewicht (kg)	6	12	13	25	30	68
Gewicht mit Verpackung (kg)	7	14	15	29	34	92

THERMOBILE INDUSTRIES BV

Konijnenberg 80 - 4825 BD Breda - Postbus 3312 - 4800 DH Breda - The Netherlands - T + 31 76 587 34 50 - F + 31 76 587 27 89
 sales@thermobile.com - www.thermobile.com - Handelskammer: Breda 20120375 - MWST. nr.: NL 8146.04.365 B01

V1601