

PRODUCTSPECIFICATIES BX/TBD 18



BX 15

BX 9

BX 3



BX 20/30



TBD 18

TBD 18 PC



TECHNISCHE SPECIFICATIES | MATEN EN GEWICHTEN

1 kW = 860 kcal/h 1 kW = 3.413 Btu/h 1 kW = 3,6 mJ/h 1 kg = 1,2 l/h

MODEL	BX 3	BX 9	BX 15	BX 20	BX 30	TBD 18	TBD 18 PC
Bestelnummer	40.107.005	40.107.015	40.107.020	40.107.021	40.107.022	40.017.100	40.017.000
Ongedieptebeijding							*
Capaciteit (kW)	3	9	15	20	30	18	18
Instelbereik (kW)	0-2-3	0-4,5-9	0-7,5-15	0-10-20	0-20-30	0-9-18	0-9-18
Aansluitspanning (V)	230	3x400	3x400	3x400	3x400	3x400	3x400
Opgenomen vermogen (A)	8,9-13,2	6,8-13,3	11,2-21,9	15-29,5	43,4	14-26	14-26
Delta T (°C)	38	36-28	42	32	47-34	20	20
Luchtverplaatsing (m³/h)	220	700-900	1.000	1.750	1.900	3.960	3.960
230 volt stekker	*						
400 volt 16 Amp stekker		*					
400 volt 32 Amp stekker			*			*	*
Thermostaat ingebouwd	*	*	*	*	*	*	*
Externe thermostaataansluiting						*	*
Draaggreep	*	*	*	*	*		
Ophangbeugel	*	*	*				
Wielset						*	*
Afm. gemonteerd LxBxH (cm)	37x28x33	37x35x45	39x52x49	61x57x57	61x57x57	176x70x83	176x70x83
Afm. verpakt LxBxH (cm)	36x28x34	40x36x49	40x36x49	51x44x69	51x44x69	120x87x105	120x87x105
Gewicht (kg)	6	12	13	25	30	68	68
Gewicht verpakt (kg)	7	14	15	29	34	92	92

THERMOBILE INDUSTRIES BV

Konijnenberg 80 - 4825 BD Breda - Postbus 3312 - 4800 DH Breda - Nederland - T + 31 76 587 34 50 - F + 31 76 587 27 89
sales@thermobile.com - www.thermobile.com - K.V.K.: Breda 20120375 - B.T.W. nr.: NL 8146.04.365 B01

v1602