




ITA-35R | Oil fired heater with flue connection



FEATURES

- High efficiency heat exchanger (91% Min).
- Outlet temperature with ΔT of about 50°C.
- Out of the box with flue pipe, roomthermostat with 10m cable and a jerrycan connection.
- Equipped with a high pressure pump for diesel or paraffin with a 2-way pipe system.
- Equipped with "ventilation-only" setting.

ADVANTAGES

- Durable phosphated body panels with powder coating.
- Maintenance friendly and easy to install and operate.
- Air hoses can be mounted in order to supply heat to specific areas.

APPLICATIONS

Heating of tents, emergency shelters, field hospitals.

ACCESSORIES




Warm-air hose



Distributionhead

WORKING PRINCIPLE

Indirect diesel fired heater that produces 100%, clean and dry, warm air by blowing air alongside a heat exchanger with a powerful axial fan.



TECHNICAL SPECIFICATIONS

1 kW = 860 kcal/hr

1 kW = 3.413 Btu/hr

1 kW = 1.2 l/hr

1 kW = 3.6 MJ/hr

ITA SERIES		35R
Heat output (kW)		24.8
Fuel consumption (l/hr)		2.4
Heated airflow (m ³ /hr)		1500
Power consumption (A) 230V		1.3A
Thermostat connection		✓
Max. ventilator back pressure (Pa)		150
Outlet cone Ø (mm)		300
Flue connection Ø (mm)		150
Dimensions (L*W*H) cm		124*58*62
Weight (kg)		48kg
Item number		41.352.000